

Dual Indicator Hour Meter TH40



TH40 Dual Indicator Hour Meter



Capable of measuring both the total time and a specific period of time

Features

- Upgraded composite function**
 In a single hour meter, the upper display shows measurement specified-period and the lower display shows the accumulated measured time.
- High-performance compact synchronous motor**
- Common for 50/60 Hz power frequency**
 A lever is used to select 50 Hz or 60 Hz. There is no need to rearrange the control panel and other signal destinations.
- Flat terminals for easy wiring**
 To weld the #187 flat connection terminals (receptacles), please use a "YC-051" tool manufactured by J.S.T. Mfg. Co., Ltd.
- Rotary indicator (Clockwise, one rotation per 2 minutes)**

DIN48

PRODUCT TYPES

Type	Operating voltage	Model No.		Operating voltage	Model No.		Operating voltage	Model No.	
		Silver panel	Black panel		Silver panel	Black panel		Silver panel	Black panel
TH40 series	100 V AC	TH401S	TH401	24 V AC	TH404S	TH404	115 to 120 V AC	TH407S	TH407
	200 V AC	TH402S	TH402	48 V AC	TH405S	TH405	220 V AC	TH408S	TH408
	12 V AC	TH403S	TH403	110 V AC	TH406S	TH406	240 V AC	TH409S	TH409

Disclaimer

The applications described in the catalog are all intended for examples only. The purchase of our products described in the catalog shall not be regarded as granting of a license to use our products in the described applications. We do NOT warrant that we have obtained some intellectual properties, such as patent rights, with respect to such applications, or that the described applications may not infringe any intellectual property rights, such as patent rights, of a third party.

Panasonic
INDUSTRY

Panasonic Industry Co., Ltd.

Industrial Device Business Division

7-1-1, Morofuku, Daito-shi, Osaka 574-0044, Japan

industrial.panasonic.com/ac/e/