

# TH40 Dual Indicator Hour Meter

Related Information

■ General terms and conditions..... F-3 ■ Selection guide ..... P.1411~



[panasonic.net/id/pidsx/global](http://panasonic.net/id/pidsx/global)

**Capable of measuring both the total time and a specific period of time**

## Features

- Upgraded composite function**  
 In a single hour meter, the upper display shows measurement specified-period and the lower display shows the accumulated measured time.
- High-performance compact synchronous motor**
- Common for 50/60 Hz power frequency**  
 A lever is used to select 50 Hz or 60 Hz. There is no need to rearrange the control panel and other signal destinations.
- Flat terminals for easy wiring**  
 To weld the #187 flat connection terminals (receptacles), please use a "YC-051" tool manufactured by J.S.T. Mfg. Co., Ltd.
- Rotary indicator (Clockwise, one rotation per 2 minutes)**

DIN□48

## PRODUCT TYPES

Type	Operating voltage	Model No.		Operating voltage	Model No.		Operating voltage	Model No.	
		Silver panel	Black panel		Silver panel	Black panel		Silver panel	Black panel
TH40 series	100 V AC	TH401S	TH401	24 V AC	TH404S	TH404	115 to 120 V AC	TH407S	TH407
	200 V AC	TH402S	TH402	48 V AC	TH405S	TH405	220 V AC	TH408S	TH408
	12 V AC	TH403S	TH403	110 V AC	TH406S	TH406	240 V AC	TH409S	TH409

FIBER SENSORS

LASER SENSORS

PHOTOELECTRIC SENSORS

MICRO PHOTOELECTRIC SENSORS

AREA SENSORS

SAFETY LIGHT CURTAINS / SAFETY COMPONENTS

PRESSURE / FLOW SENSORS

INDUCTIVE PROXIMITY SENSORS

PARTICULAR USE SENSORS

SENSOR OPTIONS

SIMPLE WIRE-SAVING UNITS

WIRE-SAVING SYSTEMS

MEASUREMENT SENSORS

STATIC CONTROL DEVICES

LASER MARKERS

PLC

HUMAN MACHINE INTERFACES

ENERGY MANAGEMENT SOLUTIONS

FA COMPONENTS

MACHINE VISION SYSTEMS

UV CURING SYSTEMS

Timers

Time Switches

Counters

Hour Meters

Options

Limit Switches

Temperature Controllers

Solenoids

Fan Motors

Selection Guide

LH2H

TH63/TH64

TH13/TH23

TH14/TH24

TH40

TH8