

Multi-range Timer S1DXM-A / S1DXM-M



1DXM-A/M Multi-range Timer



Compact analog timers featuring multi-functions

S1DXM-A multi-range timer (Power ON-delay type), **S1DXM-M** multi-range timer (4 operation mode type)

Features

- · Multiple functions built in
- Model No. consolidation (The lineup consists of 64 easy-to choose models)
- Cadmium-free contacts used
- Operation mode and time range switches are on front panel (Operation mode switch on S1DXM-M series only)
- Reasonable price

Time selectable Mode selectable IP40

PRODUCT TYPES

S1DXM-A multi-range timer without MODE switch

Operation mode (fixed): Power ON-delay

Operating voltage	Time range	Timed-out 2 Form C	Timed-out 4 Form C Model No.		
	Time range	Model No.			
12 V DC	0.05 s to 10 min	S1DXM-A2C10M-DC12V	S1DXM-A4C10M-DC12V		
	0.2 s to 30 min	S1DXM-A2C30M-DC12V	S1DXM-A4C30M-DC12V		
	0.5 s to 60 min	S1DXM-A2C60M-DC12V	S1DXM-A4C60M-DC12V		
	0.05 min to 10 hr	S1DXM-A2C10H-DC12V	S1DXM-A4C10H-DC12V		
24 V DC	0.05 s to 10 min	S1DXM-A2C10M-DC24V	S1DXM-A4C10M-DC24V		
	0.2 s to 30 min	S1DXM-A2C30M-DC24V	S1DXM-A4C30M-DC24V		
	0.5 s to 60 min	S1DXM-A2C60M-DC24V	S1DXM-A4C60M-DC24V		
	0.05 min to 10 hr	S1DXM-A2C10H-DC24V	S1DXM-A4C10H-DC24V		
100 to 120 V AC	0.05 s to 10 min	S1DXM-A2C10M-AC120V	S1DXM-A4C10M-AC120V		
	0.2 s to 30 min	S1DXM-A2C30M-AC120V	S1DXM-A4C30M-AC120V		
	0.5 s to 60 min	S1DXM-A2C60M-AC120V	S1DXM-A4C60M-AC120V		
	0.05 min to 10 hr	S1DXM-A2C10H-AC120V	S1DXM-A4C10H-AC120V		
200 to 220 V AC	0.05 s to 10 min	S1DXM-A2C10M-AC220V	S1DXM-A4C10M-AC220V		
	0.2 s to 30 min	S1DXM-A2C30M-AC220V	S1DXM-A4C30M-AC220V		
	0.5 s to 60 min	S1DXM-A2C60M-AC220V	S1DXM-A4C60M-AC220V		
	0.05 min to 10 hr	S1DXM-A2C10H-AC220V	S1DXM-A4C10H-AC220V		

Note: 48 V DC, 100 to 110 V DC, 24 V AC and 220 to 240 V AC types are made to order. Please inquire for details. A socket line holding clip (ADX28005) is not included with the product. Please purchase separately.

S1DXM-M multi-range timer with MODE switch

Operation mode (switchable): Power ON-delay, Power Flicker OFF start, Power Flicker ON start, Power One-shot

Operating voltage	Time range	Timed-out 2 Form C	Timed-out 4 Form C			
	Time range	Model No.	Model No.			
12 V DC	0.05 s to 10 min	S1DXM-M2C10M-DC12V	S1DXM-M4C10M-DC12V			
	0.2 s to 30 min	S1DXM-M2C30M-DC12V	S1DXM-M4C30M-DC12V			
	0.5 s to 60 min	S1DXM-M2C60M-DC12V	S1DXM-M4C60M-DC12V			
	0.05 min to 10 hr	S1DXM-M2C10H-DC12V	S1DXM-M4C10H-DC12V			
	0.05 s to 10 min	S1DXM-M2C10M-DC24V	S1DXM-M4C10M-DC24V			
24 V DC	0.2 s to 30 min	S1DXM-M2C30M-DC24V	S1DXM-M4C30M-DC24V			
	0.5 s to 60 min	S1DXM-M2C60M-DC24V	S1DXM-M4C60M-DC24V			
	0.05 min to 10 hr	S1DXM-M2C10H-DC24V	S1DXM-M4C10H-DC24V			
	0.05 s to 10 min	S1DXM-M2C10M-AC120V	S1DXM-M4C10M-AC120V			
100 to 120 V AC	0.2 s to 30 min	S1DXM-M2C30M-AC120V	S1DXM-M4C30M-AC120V			
100 to 120 v AC	0.5 s to 60 min	S1DXM-M2C60M-AC120V	S1DXM-M4C60M-AC120V			
	0.05 min to 10 hr	S1DXM-M2C10H-AC120V	S1DXM-M4C10H-AC120V			
200 to 220 V AC	0.05 s to 10 min	S1DXM-M2C10M-AC220V	S1DXM-M4C10M-AC220V			
	0.2 s to 30 min	S1DXM-M2C30M-AC220V	S1DXM-M4C30M-AC220V			
	0.5 s to 60 min	S1DXM-M2C60M-AC220V	S1DXM-M4C60M-AC220V			
	0.05 min to 10 hr	S1DXM-M2C10H-AC220V	S1DXM-M4C10H-AC220V			

Note: 48 V DC, 100 to 110 V DC, 24 V AC and 220 to 240 V AC types are made to order. Please inquire for details. A socket line holding clip (ADX28005) is not included with the product. Please purchase separately.

TIME RANGE SETTING

Туре		Time	Time scale Time unit		Min. scale	Max. scale	Setting range				
	10 M type			S	m	0.05	1	0.05 to 1 s	0.5 to 10 s	0.05 to 1 m	0.5 to 10 m
S1DXM-A	30 M type	×1 ×	×10	×10 S	m	0.2	3	0.2 to 3 s	2 to 30 s	0.2 to 3 m	2 to 30 m
(ADX21 series)	60 M type		*10	s	m	0.5	6	0.5 to 6 s	5 to 60 s	0.5 to 6 m	5 to 60 m
	10 H type			m	h	0.05	1	0.05 to 1 m	0.5 to 10 m	0.05 to 1 h	0.5 to 10 h
S1DXM-M	10 M type		×10 -	s	m	0.05	1	0.05 to 1 s	0.5 to 10 s	0.05 to 1 m	0.5 to 10 m
	30 M type	×1		S	m	0.2	3	0.2 to 3 s	2 to 30 s	0.2 to 3 m	2 to 30 m
(ADX27 series)	60 M type	- ^'		S	m	0.5	6	0.5 to 6 s	5 to 60 s	0.5 to 6 m	5 to 60 m
	10 H type			m	h	0.05	1	0.05 to 1 m	0.5 to 10 m	0.05 to 1 h	0.5 to 10 h

Disclaimer

The applications described in the catalog are all intended for examples only. The purchase of our products described in the catalog shall not be regarded as granting of a license to use our products in the described applications. We do NOT warrant that we have obtained some intellectual properties, such as patent rights, with respect to such applications, or that the described applications may not infringe any intellectual property rights, such as patent rights, of a third party.



Panasonic Industry Co., Ltd.

Industrial Device Business Division 7-1-1, Morofuku, Daito-shi, Osaka 574-0044, Japan industrial.panasonic.com/ac/e/